

## Multi-Purpose Aggregate

### DESCRIPTION:

This is graded silica aggregates, designed to be spread into a desired non-skid system. Available in coarse, medium and fine particle sizes. Suitable as anti-skid material in a wide range of coating systems in atmospheric environments. Suitable on any type of surface, depending on the specific coating system.

### Particle Size:

- Fine : 0.0 - 0.3 mm
- Medium : 0.4 - 0.8 mm
- Coarse : 0.6 - 1.4 mm

Paint Type	Product Type	Product mixing	Colour	Pack Size
	Aggregates	Single Pack	Wide range of attractive colours	25KG

### **Recommended Use**

Recommended for warehouses, garages, dairies, factories, laboratories, aircraft hangars, food, beverage and plant rooms where non-slip properties are required. The spreading is to take place in the wet film during application

### **Technical Data**

Volume Solid	: 100 % by weight (The provided data is typical for factory produced products, subject to slight variation depending on colour.)
Shelf Life	: 48 months at 23 °C
Storage	The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.



**Health and Safety**

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

**Caution**

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Citypaint's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible City Paints' representative for approval before commencing the work.

**Additional Information**

If required City Paints Multi-purpose Aggregate can be used with city paints Topcoat.

Aggregate is cast on to the wet first coat of the material until the whole surface is covered. Distribute the product from a container eg. distribution sieve, that will allow the aggregate to fall directly onto the wet coating.

Once the first coat has dried, remove the excess aggregate from the surface by vacuum or sweeping. The aggregate can be reused if clean.

Apply the final coat to the desired thickness.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : CITY PAINTS Customer Service  
4492 9952(Main Line)  
[www.city-paints.com](http://www.city-paints.com)