

# **Exterior Putty Powder**

# **Description**

City Paints Exterior Putty Powder is a special cement-based formula ideal for repairing cracks, holes and gaps in exterior rendering, brick, stone, wood and most other building materials. Easy to mix and simple to use. Does not shrink or crack. Has excellent adhesive properties which keep the filler firmly in position and allows a wide range of applications including the setting of non-structural bolts.

## **Directions**

Preparation: Ensure surfaces to be filled are clean, dry and dust free. For best results brush out loose material and dust from crack or hole to be filled. Moisten absorbent surfaces. Touch in nail heads with an oil-based paint to prevent rusting.

Mixing: Only mix an amount that can be used within 60 minutes. Add approximately 2.5 parts filler to 1 part cold water and mix until smooth. Always mix the filler in a clean container as a dirty container can contaminate the filler and affect the drying time.

Application: Press filler firmly into the area to be filled and remove any excess. Fill large deep holes in stages. Smooth over using a wet knife, scraper or trowel. Do not use thinly over large areas. Do not use if frost or freezing conditions are expected.

Finish: After setting overnight the filler can be left un-painted or alternatively if painting over the repair use an oil-based paint before any further paint is applied. Dries grey.

#### **Cleaning & Storage**

All tools and mixing bowls should be cleaned with warm water before filler sets. STORE IN A DRY PLACE, KEEPING SACHET CLOSED

#### **Health and Safety**

See MSDS for full information.

## **Technical Data**

Measurement	Value	Test Method
Physical State	Powder	Visual
Colour	White	Visual
Odour	None	
Flash point	Not Applicable	
Viscosity	2500 - 3200	Mix Ratio 380g to 80g Water
рН	11.5 – 12.5	

Packing: 20kg

# **Safety Precautions**

- Keep container tightly closed and keep out of reach children or away from food and drink.
- Ensure good Ventilation during application and drying.
- When applying paint, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- Paint must always be stored in a cool place.
- When transporting paint, care must be taken. Always keep container in a secure upright position.
- Dispose off any paint waste in accordance with the appropriate Environment Quality Regulations.