

# MATERIAL SAFETY DATA SHEET

Page 1 of 2 Updated  
1st, Feb 2020

PRODUCT: **JOINT FLEX SEALER-Silane/Siloxane Based**

## COMPANY DETAILS

**Company Details** City Paints Trading & Contracting Co.,  
**Address** New Industry area, Street 3, Gate 174  
**Telephone/Fax** Tel (974) 44929952 Fax (974) 44160411  
**Emergency Telephone** +974 30216516  
**Other Information** The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in this material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

## IDENTIFICATION

**Product Name** JOINT FLEX SEALER-Silane/Siloxane  
**Other Names** Silane Sealer  
**Product Code** PD6B301A  
**UN No:**  
**Hazchem:** None allocated  
**D.G. Class:** None allocated  
**Pack. Grp.:** None allocated  
**Product Type:**  
**Major Ingredients:** Silicon, Silane based emulsion  
Water based Acrylic- Polymer  
Inert Pigments & Aggregates  
**Product Use** Protection coat for substrate, clear or tint

## PHYSICAL PROPERTIES

**Appearance:** Light Pigmented thick liquid  
**Odour:** None mell  
**Viscosity:** High  
**pH:** 9.0 - 10.0  
**Specific Gravity:** 1.35  
**Flash Point:** Non Combustible Dilutable  
**Solubility in Water:** yes

## OTHER PROPERTIES

**Volid Content** 45%  
**Auto ignition Temp.** N/Avail  
**Stability** Stable

## HEALTH HAZARD INFORMATION

### Primary Routes of Exposure:

**Inhalation:** Inhalation of vapour can cause headache, nausea, irritation of nose, throat & lungs.  
**Skin Contact:** Prolonged or repeated contact can cause skin irritation.  
**Eye Contact:** Direct contact can cause eye irritation.

**FIRST AID INFORMATION**

<b>Inhalation:</b>	Move subject to fresh air.
<b>Skin Contact:</b>	Wash affected areas thoroughly with soap & water. Consult a physician if irritation persists.
<b>Eye Contact:</b>	Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart. Consult a physician if irritation persists.
<b>Ingestion:</b>	If swallowed drink at least 2 glasses of water. Consult a physician.

**PERSONAL PROTECTION**

Use only in well ventilated areas. Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

**FLAMMABILITY**

Fire Hazards      Material is non flammable

**SAFE HANDLING INFORMATION****Storage and Transport**

**STORAGE**      Store in a cool place and out of direct sunlight. Keep containers sealed when not in use.  
Store above 4°C and below 50°C

**FIRE FIGHTING INFORMATION**

**Unusual Hazards:**      Dried film can not burn.

**Extinguishing Agents:** Use extinguishing media appropriate for surrounding fire.

**Storage Requirements:** Store out of direct sunlight.

**Spills & Clean Up:**      Contain spills with sand or earth. Remove to suitable container for disposal. Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water.

.....END OF MSDS.....