TECHNICAL DATA SHEET

DELIGHT TEXTURE

DESCRIPTION

City Paints Delight Texture is a stylish, premium-grade texture coating designed for exterior decoration. Applied by roller or trowel, it provides a luxurious textured appearance with excellent weather resistance, durability, and long-lasting colour performance.

FEATURES & BENEFITS

- Excellent film hardness, adhesion, scratch and abrasion resistance
- Non-toxic; free from lead, mercury, and heavy metals
- Excellent stain washability
- Long-lasting colours with superior UV durability
- Easy roller or trowel application
- Strong adhesion to multiple substrates
- Environmentally friendly

PRODUCT INFORMATION

Paint Type	Finish	Colour	Pack Size
Water-based Interior & Exterior	Matt	White & wide range of attractive colours	25 kg

Recommended Substrates: Cement plaster, concrete, block work, rendered surfaces, gypsum board.

TECHNICAL DATA

- **Touch Dry:** 2–4 hours (ASTM D1640)
- **Hard Dry:** 24 hours (depending on temperature & humidity)
- **Overcoating Time:** 2–4 hours (varies with texture size)
- **Specific Gravity:** 1.77 ± 2% kg/L (ASTM D1475)
- **Coverage:** 0.8–1.0 m²/kg (depends on substrate & pattern)
- **Volume Solids:** 65% ± 2% (ASTM D5201)
- **Shelf Life:** Up to 12 months (sealed container)

APPLICATION METHOD

- **Trowel / Roller / Spray**
- Thin only to improve workability (max 2% water)
- Best performance when applied without dilution

RECOMMENDED COATING SYSTEM

Coat	Product	Coats
Sealer / Primer	City Paints Penetrating Sealer / Interior Primer / Acrylic Primer	1
Topcoat	City Paints Texture Paints	2

Address: Ind. Area, AR Rayyan Doha, Qatar
Email: info@city-paints.com
Tel: +974 3098 8841

25-March-2025
TDS0041

SURFACE PREPARATION

- Remove loose paint, chalk, dust, and contaminants
- Repair cracks and uneven areas with City Paints All Purpose Joint Compound
- Sand smooth and clean thoroughly
- Ensure surface is dry, grease-free, moisture <16%, alkalinity <pH 9
- Allow all surfaces to dry completely before painting

CLEANING

Clean tools and equipment with **water** immediately after use.

SAFETY PRECAUTIONS

- Keep container tightly closed and away from children, food, and drink
- Ensure proper ventilation during application and drying
- Wear eye protection
- Rinse eyes with plenty of water if contact occurs
- Wash skin with soap and water
- Store in a cool place
- Transport upright
- Dispose of waste according to environmental regulations

NOTE

Theoretical coverage is calculated as:

$$\left[\frac{Volume\ Solid\ \%\ x\ 10}{Dry\ Film\ Thickness}\right] = m^2/lit/coat$$

Actual coverage varies due to substrate porosity, application method, dilution, and film thickness.

DISCLAIMER

Information is based on laboratory testing and practical experience. As application conditions vary, City Paints guarantees only the product quality. Specifications may change without notice.

Address: Ind. Area, AR Rayyan Doha, Qatar
Email: info@city-paints.com
Tel: +974 3098 8841