TECHNICAL DATA SHEET

ELEGANT TEXTURE (Medium, Fine , Coarse)

DESCRIPTION

City Paints Elegant Texture is a durable, premium-grade exterior wall coating that provides a tough yet stylish vintage finish. It offers strong resistance to dirt, algae, fungus, fading, and chalking—keeping exterior facades looking new for longer.

FEATURES & BENEFITS

- Excellent film hardness, adhesion, scratch & abrasion resistance
- Resistant to mud-cracking
- Non-toxic; free from lead, mercury, and heavy metals
- Excellent stain washability
- Anti-fungus
- Long-lasting colours
- Low splatter
- Easy application with multiple pattern options
- Excellent adhesion and colour durability
- Environmentally friendly

PRODUCT INFORMATION

Paint Type	Finish	Colour	Pack Size
Water-based Interior & Exterior	Matt	White & wide range of attractive colours	25 kg

Recommended Substrates: Cement plaster, concrete, block work, rendered surfaces, gypsum board.

TECHNICAL DATA

- **Touch Dry:** 1–2 hours (ASTM D1640)
- **Hard Dry:** 24 hours (varies with temperature & humidity)
- **Overcoating Time:** 2–4 hours (depends on texture size)
- **Specific Gravity:** 1.87 ± 2% kg/L (ASTM D1475)
- **Coverage:** 0.4–0.8 m²/kg (depends on substrate & pattern)
- **Volume Solids:** 75% ± 2% (ASTM D5201)
- **Shelf Life:** Up to 12 months (sealed container)

APPLICATION METHOD

- **Trowel / Roller / Spray**
- Thin only to improve workability (max 2% water)
- Best performance when applied without dilution

RECOMMENDED COATING SYSTEM

Coat	Product	Coats
Sealer / Primer	City Paints Penetrating Sealer / Interior Primer / Acrylic Primer	1
Topcoat	City Paints Elegant Texture Paint	2

Address: Ind. Area, AR Rayyan Doha, Qatar
Email: info@city-paints.com
Tel: +974 3098 8841

25-March-2025
TDS0042

TECHNICAL DATA SHEET

ELEGANT TEXTURE (Medium, Fine , Coarse)

SURFACE PREPARATION

- Remove loose paint, chalk, dust, and contaminants
- Repair cracks and uneven areas with City Paints All Purpose Joint Compound
- Sand smooth and clean thoroughly
- Ensure surface is dry, grease-free, moisture <16%, alkalinity <pH 9
- Allow surfaces to dry completely before painting

CLEANING

Clean tools and equipment with **water** immediately after use.

SAFETY PRECAUTIONS

- Keep container tightly closed and away from children, food, and drink
- Ensure good ventilation during application and drying
- Wear eye protection
- Rinse eyes with plenty of water if contact occurs
- Wash skin with soap and water
- Store in a cool place
- Transport upright
- Dispose of waste according to environmental regulations

NOTE

DISCLAIMER

Information is based on laboratory testing and practical experience. As application conditions vary, City Paints guarantees only the product quality. Specifications may change without notice.

Address: Ind. Area, AR Rayyan Doha, Qatar
Email: info@city-paints.com
Tel: +974 3098 8841

25-March-2025
TDS0042