TECHNICAL DATA SHEET

STUCCO PUTTY

DESCRIPTION

City Paints Stucco Putty is designed for wall pre-treatment and gap filling. It provides high adhesion, long-term toughness, easy application, and excellent stability, producing a smooth surface for subsequent coatings.

PRODUCT FEATURES

- Absorb harmful formaldehyde
- Non-toxic; free from lead, mercury, heavy metals
- Anti-fungus and mold-resistant
- Low splatter
- Easy application
- Excellent coverage and hiding power
- Strong adhesion
- Ideal base for topcoats

PRODUCT INFORMATION

Paint Type	Finish	Colour	Pack Size
Interior	Matt	White	USG & 25 KG

Recommended Substrates: Cement plaster, concrete, block work, rendered surfaces, gypsum board. Substrate must be sound and defect-free.

TECHNICAL DATA

- **Touch Dry:** 30 minutes at 30°C
- **Hard Dry:** 3–5 hours at 30°C
- **Recoating Time:** 4–5 hours
- **Dry Film Thickness:** 85–130 µm per coat
- **Number of Coats:** 2
- **Coverage:** 4–6 m²/L or 2.8–3 m²/kg per coat
- **Volume Solids:** ~69% ±2% (white)
- **Shelf Life:** Up to 12 months (sealed container)

APPLICATION METHOD

- **Tool:** Putty knife
- **Dilution:** Max 5% water (best performance without dilution)

RECOMMENDED COATING SYSTEM

Coat	Product	Coats
Sealer / Primer	City Paints Primer Products	1
Topcoat	City Paints Stucco Putty	2 (Smoothening Coats)

Address: Ind. Area, AR Rayyan Doha, Qatar
Email: info@city-paints.com
Tel: +974 3098 8841

25-March-2025
TDS0031

SURFACE PREPARATION

- Remove loose paint, chalk, dust, and contaminants
- Repair cracks and uneven areas with City Paints All Purpose Joint Compound
- Sand puttied areas smooth
- Ensure surface is clean, dry, and free from grease
- Do not paint when moisture >16% or alkalinity >pH 9
- Spot prime with City Paints Interior Sealer

CLEANING

Clean tools with **water** immediately after use.

SAFETY PRECAUTIONS

- Keep container tightly closed and away from children, food, and drink
- Ensure good ventilation during application and drying
- Wear eye protection
- Rinse eyes with plenty of water if contact occurs
- Wash skin with soap and water
- Store in a cool place
- Transport upright
- Dispose of waste according to environmental regulations

NOTE

Theoretical coverage is calculated as:

$$\left[\frac{Volume\ Solid\ \%\ x\ 10}{Dry\ Film\ Thickness}\right] = m^2/lit/coat$$

Actual coverage varies due to substrate porosity, dilution, method, and film thickness.

DISCLAIMER

Information is based on laboratory tests and practical experience. As application conditions vary, City Paints guarantees only product quality. Specifications may change without notice.

Address: Ind. Area, AR Rayyan Doha, Qatar
Email: info@city-paints.com
Tel: +974 3098 8841